



KRISPOL

Our new products include formulas that allow for comprehensive care of your garage and industrial doors. Read the descriptions below.



Active foam is a multi-purpose agent. Designed for cleaning various surfaces, including laminated, glass, rubber and plastic elements. Effectively removes dust and greasy stains without leaving streaks in the place of cleaning.



Formula for the cleaning and maintenance of the shell and other parts made of plastic and rubber. It features an antistatic effect and protects the surface against dust, dirt and moisture. It also restores the original appearance and colours of any cleaned elements.



Silicone is a formula for the maintenance and care of rubber, plastic and steel elements. It facilitates the operation of locks, hinges and guides. Ideal for use on garage and industrial doors, windows and door seals. Gives shine and provides protection against cracking and crumbling.



Dry lubricant is a formula that contains PTFE particles which adhere to steel elements and thus reduce friction. It protects against corrosion and is resistant to low and high temperatures. Intended for lubrication of elements of industrial doors, garage doors, doors and windows as well as gear mechanisms.

Step-by-step maintenance *of garage and industrial* doors

1.



Clean hard-to-reach areas under gaskets between sections - preferably with compressed air. Wipe the surface to be cleaned with a damp cloth or rinse with a gentle stream of water. Do not use a high pressure washer. Then apply the active foam on the dry surface from a distance of 15-20 cm and leave for at least 60 seconds to dry. Wipe with a dry, soft cloth.

Important: Strong scrubbing must be strictly avoided as it may damage the surface.

3.



Apply silicone on the gaskets from a distance of 15-20 cm. Leave to dry.

2.



Apply the garage door shell maintenance formula on the cleaned surface using a soft and clean microfiber cloth. The formula may be also applied by spraying it from a distance of 15-20 cm and wiping with a clean, soft cloth.

4.



Apply the dry lubricant onto the hinge pins and rollers.

Note: Under no circumstances **lubricate the guiding tracks**. Clean their interior from dust and dirt only.

We're focused
on *garage*
& *industrial* doors

krispol.eu

